











AT-22/22

75%

								
								
	7.2 m.	11.95 m.	16.7 m.	21.45 m.	27.45 m. (6 m.)			
				0°	15°	30°		
3	20	18.2						3
4	18.4	16.5	14.5					4
5	13.8	13.5	10.8	8.5				5
6		8.8	8.1	7.4	4.35			6
7		6.65	6.65	6.35	4.35			7
8		5.4	5.4	5.2	3.8	3.8		8
9		4.35	4.35	4.35	3.5	3.5		9
10		3.75	3.75	3.75	3.1	3.1	3.1	10
11			3.3	3.3	2.8	2.8	2.8	11
12			2.9	2.9	2.6	2.6	2.6	12
13			2.35	2.35	2.4	2.4	2.4	13
14			1.95	1.95	2.15	2.15	2.15	14
15				1.7	1.95	1.95	1.95	15
16				1.5	1.75	1.75	1.75	16
17				1.25	1.5	1.5	1.5	17
18				1.1	1.35	1.35	1.35	18
19				0.85	1.15	1.15	1.15	19
20					1	1	1	20
21					0.85	0.85	0.85	21
22					0.7	0.7	0.7	22
23					0.6	0.6	0.6	23
24					0.55	0.55	0.55	24

			
	6	9.6	
3	6	9.6	3
4	4.25	7.3	4
5	2.1	5	5
6	1.75	3.6	6
7	1.2	2.7	7
8	1.05	2.25	8
9	0.85	1.85	9
10	0.75	1.5	10
11		1.3	11
12		1.05	12
13		0.85	13
14		0.7	14

- Las capacidades de carga indicadas al 75% , estan referidas a la norma DIN-15019-h2.
- Los pesos de ganchos y eslingas deben deducirse de todas las cargas.



DIAGRAMA DE ALCANCES
GRUA TIPO: AT-22/22

